

# DP-GSM

GSM (2G) / UMTS (3G) Door Intercoms



## DP-GSM-SM

Surface mount design



### Features:

- Vandal proof Stainless steel case
- 1 or 2 call buttons
- 2G or 3G communication
- 2 controllable output (relay and power)
- Gate controlling by free call, up to 100 users
- Gate controlling by mobile app, up to 1000 users
- Remote management via Internet, by WEB browser

### Technical specifications:

- Dimensions: 67x157x35 (SM) or 87x176x23 (FM)
- Ingress Protection: IP54
- Power supply: DC 12V, minimum 1A
- Network communications: GSM(2G), UMTS(3G)
- SIM card size: 3FF Micro-SIM (15x12mm)

### Accessories:

- DP-GSM Intercom with front plate
- Mounting frame SM or FM
- Security screw + screwdriver bit
- Antenna 2G or 3G
- USB cable
- Power supply DC-12V / 1.5A
- Antenna mount bracket
- Wall mounting screws

### Types:

- DP-GSM-SM-1
- DP-GSM-SM-2
- DP-GSM/3G-SM-1
- DP-GSM/3G-SM-2
- DP-GSM-FM-1
- DP-GSM-FM-2
- DP-GSM/3G-FM-1



## DP-GSM-FM

Flush mount design



### Software tools:

- PULOWARE control mobile App  
IOS and Android
- Remote management IoT server access

[www.puloware.com](http://www.puloware.com)

