ITAN 45

DOOR INTERCOM FOR MOBILE NETWORK











Variants







Technical parameters:

Electronic features

9-30 VDC Power supply Current consumption Idle: 0.1A

Maximum: 0.5A

Peak for driving the door lock: 1.5A

9-24VDC according to the supply voltage / 1.5A peak with protection Voltage output

Relay output Potential-free N/O contact, Max. load: 1A / 60VDC

Network connection

Network type Primary: VoLTE (4G) / Fallback: GSM (2G)

Bands LTE (4G): B1/B3/B5/B7/B8/B20

EMEA region only

Audio features

Microphone 1 integrated microphone

Amplifier 1W (Class D)

Speaker 1 integrated, max. 2W

Audio transmission Full duplex

Operating features

Phone numbers to call 2 | primary and secondary Call setup time 3 sec (VoLTE) / 8 sec (GSM) Control with caller ID 20 | Relay / Voltage output

Control with keypad 4 fixed code and 4 temporary codes with expiry datel

Setting method via WIFI hotspot / via USB

via WEB / via SMS Remote management

Appearance

Material Anodised aluminium case (A6061) Display Electronic paper (active matrix display)

Dimensions 80mm x 140mm x 23,5mm

430 g

Weight

Operating temperature -30°C / +60°C (with active internal heating)

IP protection **IP65**